








## Electronic control device for gas burners of heating installations

**Patent number:** EP0614047  
**Publication date:** 1994-09-07  
**Inventor:** PALLEK ANTON DIPL-ING FH (DE);  
 SCHWENDEMANN ECKHARD DIPL-ING (DE)  
**Applicant:** LANDIS & GYR BUSINESS SUPPORT (CH)  
**Classification:**  
 - international: F23N5/20; F23N1/10; F23N3/08  
 - european: F23N1/10B; F23N3/08B; F23N5/20B  
**Application number:** EP19930114750 19930914  
**Priority number(s):** CH19930000662 19930305

### Also published as:

 EP0614047 (B1)  
 DE9310458U (U1)


### Cited documents:

 EP0073717  
 DE4007699  
 JP2021123  
 JP1302027  
 JP63318417  
 more >> -

Report a data error here

### Abstract of EP0614047

To simplify an electronic control device for gas burners of heating installations, the microcomputer MC of the automatic firing unit is extended to take over tasks from the heating regulator. The microcomputer or the device equipped therewith is provided with a signal generator SG, a comparator Ve, a controller R and a temperature watchdog. The signal generator generates, in particular, pulse-width-modulated control signals SST, which are used for controlling a D.C. motor M, which is used as drive element for an air blower G. The comparator compares rotational speed current values of the blower generated by a rotational speed sensor Fn with rotational speed desired values or limiting values stored in the memory SP and, as a function of the type and/or the magnitude of the difference values, triggers control signals SST or influences the latter. Furthermore, the microcomputer outputs control signals to the D.C. motor of the blower during the operational time of the burner as a function of parameters controlling the boiler temperature TK, and takes over temperature watchdog tasks.



Data supplied from the esp@cenet database - Worldwide

BEST AVAILABLE COPY